



plasticizer present in an amount sufficient to impart flexibility to said rigid polymer.

10. A high-pressure hose according to claim 9, wherein said rigid polymer comprises PVC.

11. A pressure-washing apparatus comprising: a source of pressurized water; an operator wand; and a hose fluidically connecting said operating wand to said source, said hose comprising an inner core comprising a flexible material and defining a fluid-carrying conduit; a flexible reinforcing sheath covering said core; and a jacket covering said sheath, said hose having a minimum bend radius no greater than about 38 mm at ambient pressure, and a burst pressure of at least about 8000 psi.

12. A pressure-washing apparatus according to claim 11, said hose having a burst pressure of at least about 9000 psi.

13. A pressure-washing apparatus according to claim 11, said hose having a burst pressure of at least about 10,400 psi.

14. A pressure-washing apparatus according to claim 11, said hose having a burst pressure of at least about 12,000 psi.

15. A pressure-washing apparatus according to claim 11, said hose having a volumetric expansion of no more than about 4.0 cc/ft. at a pressure of 25% of said minimum burst pressure.

16. A pressure-washing apparatus according to claim 11, said hose having an elongation of no more than about 3% at a pressure of 25% of said minimum burst pressure.

352020 2222050

18. A pressure-washing apparatus according to claim 11, wherein said hose has a minimum impulse value of at least about 30,000 cycles.

20. A pressure-washing apparatus according to claim 19, wherein said rigid polymer comprises PVC.